

Simon Door Only Installation With Half Surface Hinges

Caution to Installer: Note Labels Indicating “Hinge Side” and “Top of Door”

This door has a factory applied gelcoat finish unless supplied with a primer finish. It will never need to be painted. **Do not mar or damage surface.** The owner will expect you to exercise care to preserve the finish. Have sufficient help as not to drag or skid the doors. Before proceeding check hinge spacing on old door against new door. If there is a discrepancy call Simon Door at toll free 866.894.7511 and ask for Customer Service.

Do not attempt to cut or modify the door dimensions in any way, as this will void the warranty.

1. Remove old door and hardware.
2. Set new door in opening. Use shims at door bottom to raise door to within 1/8 in of door header. Door should have 1/8 inch gap all around at header and jambs. Door hinges should be used to drill thru door to attach thru bolts.
3. If required shim behind jamb hinge leaves to maintain 1/8 inch clearance at strike jamb.
4. Make sure latch aligns with strike plate in door jamb.
5. Check fit all around door frame.
6. Check for freedom of swing and lock alignment. Adjust shims if necessary.

O.K. TO RELEASE _____

DATE: _____

CEO _____

CFO _____

GENERAL MGR: _____

ENGINEERING _____

PURCHASING: _____

PRODUCTION _____

NO PART OF THIS DRAWING MAY BE REPRODUCED, STORED IN A RETRIEVAL SYSTEM, OR TRANSMITTED IN ANY FORM OR BY ANY MEANS, ELECTRONIC, MECHANICAL, PHOTOCOPYING, RECORDING OR OTHERWISE, WITHOUT THE PRIOR WRITTEN CONSENT OF SIMON DOOR COMPANY LLC.

THE DATA CONTAINED IN THIS PUBLICATION IS FOR THE CONFIDENTIAL USE OF THE PURCHASER ONLY. THIS DATA IS NOT TO BE SOLD OR OTHERWISE PROVIDED TO THIRD PARTIES IN ANY FORM.

© COPYRIGHT SIMON® DOOR COMPANY LLC. 2006

PATENTS PENDING

SIMON / DOOR

COMPANY LLC.

**P.O. BOX 4557 BROWNSVILLE, TX 78523
1-866-894-7511 / FAX: (956) 831-7530**

**SIMON DOOR ONLY INSTALLATION WITH
HALF SURFACE HINGES**

PART. NO: SD-F23		PAGE: 1 OF 1	
SCALE	DWN BY	REV. #	DATE
N.T.S.	MDC	1	07/14/08